PRODUCT INFORMATION



OXIDIZING AGENT STORAGE CABINET - 60LTR, 1 DOOR, 2 SHELVES PRODUCT CODE: 5517AOA

Pratt Indoor Oxidizing Agent Storage Cabinets comply with the Australian Standard AS 4326 "The Storage and Handling of Oxidizing Agents".

This range of cabinets is for the storage of Oxidizing Agents in liquid or solid form as classified by the United Nations criteria and the ADG Code for Dangerous Goods. These include chemicals such as Hypochlorite-inorganic, Hydrogen Peroxide, Perchlorites-inorganic and Potassium Nitrate.

FEATURES AND BENEFITS:

- Constructed of double walled 1.2mm thick galvanised steel.
- 2 x 1.6mm thick, perforated, galvanised steel shelves.
- Continual piano type door hinge.
- Overlapping door edging to prevent ingress of heat.
- Adjustable shelf heights at 45mm increments.
- 2 x 50mm vent bungs with steel caps.
- Each vent incorporates steel flash arrester.
- Single self closing door with speed adjustable hydraulic closure.
- Magnetic catch to hold door in closed position to provide automatic release in the event of pressure build up.
- Recessed non lockable handle.
- External static earthing connection and 1 x bonding wire.
- Solvent resistant yellow baked powder coated finish.
- 150mm deep liquid tight sump.
- Palletized and packaged with strong cardboard carton for protection during transportation and storage.
- Oxidizing Agent diamond and other decals applied.
- Optional additional shelves available.

Weight: 62kg Capacity: 60L Doors: 1

Shelves: 2 (Inc. Base Level)

Extra Shelf: 5517-29S



EXTERNAL (mm)			INTERNAL (mm)		
HEIGHT	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH
1065	515	465	820	420	370

AS 4326 specifies a maximum of 50kg or L for Packaging Group I Oxidizing Agents.
Note: 1. Internal height is taken from the top of the sump sill/bottom shelf to the ceiling.

For total external width measurement, add 6mm per vent bung for tight clearance locations.

PER SHELF	TOTAL
6	12
4	8
4	8
2	4
1	2
1	2
30	60
	6 4 4 2 1