

Win a Free Medical Fridge or Freezer*



We are searching for the oldest working Nuline Refrigeration's medical fridge or freezer as part of our 40th Anniversary celebration.

Win a new Nuline Refrigeration's medical fridge most like your existing one.

Proudly Manufacturing in Australia and a locally owned family business.

Simply fill in the form on our website

Submissions close June 30th 2025, and the winning entrant will be notified via email and phone on July 14th 2025.

* Terms and Conditions apply



MLS 125 STATIC REFRIGERATOR



FEATURES

- Static Refrigeration System
- Voltage Free Connection
- Door Lock
- Door Ajar Alarms
- Battery Backup for Controller
- Digital Display with Built-in Alarms
- Hi/Lo Readout





2°C to 8°C



125 L



595w x 610d x 840h



+61 3 9562 3355 info@nuline.au

MLS 125 STATIC REFRIGERATOR



Model	MLS125GP	MLS125P
Gross Capacity	125 L	125 L
External Dimensions in mm (w/d/h including castors)	595 x 610 x 840	
Internal Dimensions in mm (w/d/h)	505 x 442 x 625	
Packed Dimensions in mm (w/d/h including pallet)	660 x 705 x 910	
Gross Weight - kg (packed weight)	59	
Net Weight - kg	55	
Voltage	220V	
Temperature Range	2°C to 8°C	
Ambient Temperature Range	10°C to 32°C	
Refrigerant	R600a	
Cooling System / Defrost	Static / Automatic	
Exterior Cabinet Finish	White Enamel	
Inner Liner Material	White Enamel	
Door	Glass	Solid
Door Hinge	RH	
Door Handle	Pull Handle	
Type of Controller	Digital	
Temperature Display	External	
Door Ajar Alarms	Standard	
High and Low Readout	Visual / Audible	
BMS Connectivity		
(BMS Connectivity for Remote Alarms only)	Standard	
(BMS Connectivity for 4-20mA Transmitter)	Optional	
Port Entry	Standard	
Battery Back-up for Controller	Standard	
Power Requirement	10amp GPO	
Castors	Adjustable Levelling Legs	
Adjustable Shelves	4	
Usable Shelf Area in mm (w/d)	2 x 488 x 411 2 x 488 x 276	



Nuline Refrigeration reserves the right to alter the specifications without prior notice.