

ML SERIES VACCINE REFRIGERATOR

NULINE
REFRIGERATION

FEATURES

- Fan Forced System
- Voltage Free Connection
- Door Lock
- Door Ajar Alarms
- Interior LED Lighting
- Automatic Condensate Water Disposal
- Fan Door Switch
- Data Logger Included
- Battery Backup for Controller
- Digital Display with Built in Alarms
- Hi / Lo Read Out
- Self Closing Door
- ARTG Number 269893



2°C to 8°C



29 L
59 L
125 L



445 x 500 x 550h
450 x 460 x 875h
595 x 610 x 840h

+61 3 9562 3355

info@nuline.au

www.nuline.au

+64 9 884 4181

info@nuline.co.nz

www.nuline.co.nz



ML SERIES VACCINE REFRIGERATOR



Model	ML29GP	ML59GP	ML125GP/P
Gross Capacity	29 L	59 L	125 L
External Dimensions in mm (w/d/h including castors)	445 x 500 x 550	450 x 460 x 875	595 x 610 x 840
Internal Dimensions in mm (w/d/h)	361 x 205 x 400	390 x 300 x 720	505 x 442 x 625
Packed Dimensions in mm (w/d/h including pallet)	500 x 576 x 590	525 x 560 x 900	660 x 705 x 910
Gross Weight - kg (packed weight)	32	41	59
Net Weight - kg	27	38	55
Energy Consumption	0.71 kW/h	0.81 kW/h	0.84 kW/h
Voltage	220V		
Temperature Range	2°C to 8°C		
Ambient Temperature Range	10°C to 32°C		
Refrigerant	R600a		
Cooling System / Defrost	Fan Forced / Automatic		
Exterior Cabinet Finish	Enamelled Steel		
Inner Liner Material	ABS		
Door	Glass	Glass	Glass / Solid
Door Hinge	RH		
Door Handle	Pull Handle		
Type of Controller	Digital		
Temperature Display	External		
Data Logger	Standard		
Door Ajar Alarms	Standard		
High and Low Readout	Visual / Audible		
BMS Connectivity			
(BMS Connectivity for Remote Alarms only)	Standard		
(BMS Connectivity for 4-20mA Transmitter)	Optional		
Port Entry	Standard		
Battery Back-up for Controller	Standard		
Power Requirement	10amp GPO		
Castors	Adjustable Levelling Legs		
Adjustable Shelves	2	3	4
Usable Shelf Area in mm (w/d)	2 x 376 x 190	2 x 368 x 287 1 x 378 x 190	2 x 488 x 411 2 x 488 x 276
Light	LED		

Nuline Refrigeration reserves the right to alter the specifications without prior notice.